

# DEWATERING ROLL-OFF CONTAINER



## SPECIFICATIONS

<b>FLOOR SHEET</b>	3/16" (2) PIECES BUTT WELDED
<b>CROSSMEMBERS</b>	3" STRUCTURAL CHANNEL 4.1 LBS/FT AT 16" ON CENTER
<b>LONG RAILS</b>	2" X 6" X 1/4" TUBING
<b>FRONT WHEELS</b>	8" X 6" LONG WITH GREASE ZERK <i>(FRONT WHEELS STANDARD ONLY ON CABLE)</i>
<b>REAR WHEELS</b>	8" X 10" LONG WITH GREASE ZERK
<b>SIDE SHEET</b>	10 GAUGE
<b>SIDE POSTS</b>	3" X 5" FORMED ON 24" CENTERS
<b>TARP RAIL</b>	5/8" ROUND BAR
<b>TOP RAILS</b>	3" X 4" X 7 GAUGE TUBING
<b>BULKHEAD SHEET</b>	10 GAUGE
<b>PUSH PLATE</b>	26" X 16" X 3/16"
<b>BULL NOSE</b>	SOLID 1 1/4" PLATE BURNOUT
<b>NOSE ROLLERS</b>	HEAVY DUTY MACHINED 4" DIAMETER X 6" LONG <i>WITH GREASE ZERKS</i>
<b>HOOK PLATE</b>	23" X 15" X 3/4"
<b>TAIL GATE SHEET</b>	10 GAUGE
<b>TAIL GATE FRAME</b>	VERTICAL 3" X 4" X 7 GAUGE TUBING
<b>REAR CORNER POST</b>	3 1/2" X 7" X 3/16" FORMED
<b>HINGES</b>	HEAVY DUTY WITH GREASE ZERKS <i>THREE ON 54" OR HIGHER SIDES</i>
<b>LATCHES</b>	VERTICAL LIFT HANDLE
<b>DEWATERING FEATURE</b>	CHOOSE FROM PERFORATED SIDES AND/OR FLOOR, PERMANENT OR REMOVABLE, AND 10GA OR 7GA PERFORATED STEEL
<b>PAINT</b>	INTERIOR/EXTERIOR SOLVENT BASED PRIME EXTERIOR SOLVENT BASED TOP COAT <i>COMPLETE PAINT OPTION AVAILABLE</i>



### STANDARD PAINT COLORS

BLACK



BUCKS® RED



MACK GREEN



VALVOLINE BLUE



*Custom colors may result in increased cost and lead times.*

# CONTAINER OPTIONS

Options may result in increased cost and lead times.



DUMP GATE



FALSE FLOOR



DEWATERING BASKET  
*(REMOVABLE)*



FITTINGS  
*(MANY STYLES AVAILABLE)*



LINER HOOKS



SOLID UNIT, NO GATE



DUAL HOOK-UP



TARP *(MANY STYLES AVAILABLE)*

## STANDARD DIMENSIONS

Containers can be manufactured to customer specified dimensions and may result in increased costs and lead times.

<u>Yardage</u>	<u>Floor Length</u>	<u>Inside Height</u>	<u>Width</u>
10	12'	42"	96" Outside, 88" Inside
12	12'	48"	96" Outside, 88" Inside
15	14'	48"	96" Outside, 88" Inside
20	22'	42"	96" Outside, 88" Inside
25	22'	52"	96" Outside, 88" Inside
30	22'	62"	96" Outside, 88" Inside
35	22'	72"	96" Outside, 88" Inside
40	22'	82"	96" Outside, 88" Inside
45	22'	92"	96" Outside, 88" Inside
50	24'	96"	96" Outside, 88" Inside
55	26'	96"	96" Outside, 88" Inside
60	28'	96"	96" Outside, 88" Inside