

ULTRA BOX ROLL-OFF CONTAINER



Subsidiary of Federal Signal Corporation

SPECIFICATIONS

FLOOR SHEET	1/4" BUTT WELDED
CROSSMEMBERS	3" STRUCTURAL CHANNEL 4.1 LBS/FT 12" ON CENTERS
LONG RAILS	2" x 6" x 1/4" TUBING
FRONT WHEELS	HEAVY DUTY 8" DIAMETER x 6" WIDE <i>WITH GREASE ZERK</i> <i>(FRONT WHEELS STANDARD ONLY ON CABLE)</i>
REAR WHEELS	HEAVY DUTY 8" DIAMETER x 10" WIDE <i>WITH GREASE ZERK</i>
SIDE SHEET	10 GAUGE
SIDE POSTS	3" x 5" FORMED 24" ON CENTERS
TARP RAIL	5/8" ROUND BAR
TOP RAILS	3" x 4" x 7 GAUGE TUBING
BULKHEAD SHEET	10 GAUGE
PUSH PLATE	26" x 16" x 3/16"
BULL NOSE	SOLID 1 1/4" PLATE BURNOUT
NOSE ROLLERS	HEAVY DUTY MACHINED 4" DIAMETER x 6" <i>WITH GREASE ZERK</i>
HOOK PLATE	HEAVY DUTY 23" x 15" x 1"
TAIL GATE SHEET	10 GAUGE
TAIL GATE FRAME	VERTICAL 3" x 4" x 7 GAUGE TUBING
REAR CORNER POST	3 1/2" x 7" x 3/16" FORMED
HINGES	HEAVY DUTY <i>WITH GREASE ZERK</i> <i>(THREE ON 54" OR HIGHER SIDES EXCEPT FOR BARN DOORS)</i>
LATCHES	VERTICAL LIFT HANDLE
PAINT	INTERIOR/EXTERIOR SOLVENT BASED PRIME EXTERIOR SOLVENT BASED TOP COAT <i>(COMPLETE PAINT OPTION AVAILABLE)</i>



STANDARD PAINT COLORS

Custom colors may result in increased cost and lead times.

BLACK



BUCKS® RED



MACK GREEN



VALVOLINE BLUE



B046.2304

CONTAINER OPTIONS

Options may result in increased cost and lead times.



6 OR 9 PANEL GATE




TUBING SIDE POSTS



SIDE STIFFENERS



CRASH PLATE



FULLY WELDED



INVERTED ANGLE TOP RAILS



SEALED GATE

STANDARD DIMENSIONS

Containers can be manufactured to customer specified dimensions and may result in increased costs and lead times.

<u>Yardage</u>	<u>Floor Length</u>	<u>Inside Height</u>	<u>Width</u>	<u>Estimated Weight</u>
10	12'	42"	96" Outside, 88" Inside	3600 lbs
12	12'	48"	96" Outside, 88" Inside	3800 lbs
15	14'	48"	96" Outside, 88" Inside	4200 lbs
20	22'	42"	96" Outside, 88" Inside	5800 lbs
25	22'	52"	96" Outside, 88" Inside	6200 lbs
30	22'	62"	96" Outside, 88" Inside	6500 lbs
35	22'	72"	96" Outside, 88" Inside	6900 lbs
40	22'	82"	96" Outside, 88" Inside	7300 lbs
45	22'	92"	96" Outside, 88" Inside	7700 lbs
50	24'	96"	96" Outside, 88" Inside	8400 lbs